

TECHNICAL DATA SHEET SHIELD ALUMINUM PAINT

5/13

INTRODUCTION

SHIELD ALUMINUM WALL PRIMER is a synthetic enamel primer that is easy to apply and has an excellent hiding power. SHIELD ALUMINUM WALL PRIMER paint can be used on all types of metals and wood.

APPLICATION

Before applying SHIELD ALUMINUM WALL PRIMER, the surface should be cleaned properly to remove dust, losses particles and fatty stains. SHIELD ALUMINUM WALL PRIMER can be applied on the surface by means of a roller on a spray gun.

SHIELD ALUMINUM WALL PRIMER should be diluted with up to 20% Savanna Turpentine or Azar Thinner.

COMPOSITION

SHIELD ALUMINUM WALL PRIMER is an alkyd – based synthetic enamel with a high alkyd content giving it an excellent gloss. SHIELD ALUMINUM WALL PRIMER also contains leafing aluminum paste and is 100% lead free.

Properties	Analysis
Appearance	Grey in Colour
Solid content	56 – 58%
Density	0.98
Coverage	12m ² / ltr
Dilution	15 – 20 % with Turpentine or Thinner
Gloss	60
Drying time	3 – 4 hrs Recoat Overnight

STORAGE & PACKAGING

SHIELD ALUMINUM WALL PRIMER should be stored at a temperature below 40°C. SHIELD ALUMINUM WALL PRIMER containers should not be exposed to direct sunlight.

SHIELD ALUMINUM WALL PRIMER is available in 3.6L metal containers.