

INTRODUCTION

Shield Gloss is a synthetic high-gloss enamel paint that is easy to apply and has an excellent hiding power. Shield Gloss can be used on interior and exterior Masonry surface, Metal, Steel, Wood etc.

APPLICATION

Before applying Shield Gloss, the surface should be cleaned properly to remove dust, loose particles, and fatty stains.

The application of a suitable Shield Primer is also crucial before applying the paint.

Shield Primer, Shield Gloss should be diluted with up to 20% Savana Turpentine or Azar Thinner, and applied onto the surface by means of a brush, a foam roller, or a spray gun.

FEATURES & BENEFITS

Shield Gloss is an alkyd-based synthetic enamel with a high alkyd content giving it an excellent gloss.

Shield Gloss is also highly pigmented giving it a good hiding power.

COMPOSITION

Shield Gloss is based on synthetic enamel, pigments, organic and inorganic pigments, and additives.

Shield Gloss is a 100% lead-free.

Properties	Analysis
Appearance	Wide variety of colors
Solid Content	55%
Density	1.08 g/L
Coverage	14 m ² /L
Dilution	15 - 20% with turpentine or thinner
Gloss	> 85° @ 60° Angle
	2 - 3 hours and can be recoated overnight

STORAGE & PACKAGING

Shield Gloss should be stored at a temperature below 40° C. Shield Gloss containers should not be exposed to direct sunlight.

Shield Gloss is available in 0.9L and 3.6L metal containers.