

INTRODUCTION

Shield Waterproofer is an acrylic-based water proofer that seals and protects against the damaging effects of rain. Shield Waterproofer prevents water penetration, thus, protecting the cement or plaster.

APPLICATION

Three coats of Shield Waterproofer must be applied in three different stages after surface preparation.

- First Coat: Shield Waterproofer should be diluted with 50% water and applied with a brush or a roller.
- Second Coat: Shield Waterproofer should be diluted with 30% water and applied with a brush or a roller.
- Third Coat: Shield Waterproofer should be applied directly from its container without dilution.

FEATURES & BENEFITS

Shield Waterproofer contains a high percentage of acrylic binder leading to the formation of a very resistant layer against water penetration, and forming a flexible layer that prevents the formation of cracks as a result of the expansion and contraction of cement or plaster.

Shield Waterproofer reduces the maintenance cost by improving and extending the useful life of cement or plaster.



COMPOSITION

Shield Waterproofer is an acrylic-based proofer that contains fillers, extenders and titanium dioxide.

PROPERTIES	ANALYSIS
Appearance:	Milky white color
Ph:	8.5 – 9.5
Density:	1.2 g/L
Coverage:	15 m ² /L
Dilution:	See Application
Drying Time:	30 Minutes

STORAGE & PACKAGING

Shield Waterproofer should be stored at a temperature below 40°C. Shield Waterproofer containers should not be exposed to direct sunlight.

Shield Waterproofer is available in 10L, and 20L plastic containers.