



SHIELD FUNGUS WASH

TECHNICAL DATA SHEET

AZAR CHEMICAL INDUSTRIES LTD



TECHNICAL DATA SHEET

SHIELD FUNGUS WASH

INTRODUCTION

Shield Fungus Wash is a chlorite-based solution specifically designed to remove fungus from any surface. Its special formulation effectively attacks and destroys all fungal growth, ensuring a clean and treated surface.

TECHNICAL DATA

<u>PROPERTIES</u>	<u>ANALYSIS</u>
Appearance:	Liquid
PH:	8.5
Solid Content:	N/A
Density:	0.95 g/L
Coverage:	N/A
Dilution:	N/A
Drying Time:	20 Minutes



Shield Fungus Wash

Coats (depending on thickness and severity of the fungal growth)

COMPOSITION

Base: Methylene Chloride

Additives: Wax

APPLICATION

FUNGUS WASH APPLICATION:

Shield Fungus Wash to be applied directly onto the affected surface.

Application Method: Use a brush to apply the fungus wash.

Drying time: Wait for 20 minutes to allow the solution to act on the fungus.

Scrape: Scrape the surface to remove loosened fungal growth.

Rinse: Rinse the surface thoroughly with plenty of water to wash away any residue and avoid peeling of paint.

Coats: Wait 20 minutes before apply additional coats, if needed, depending on the thickness and severity of the fungal growth.

Note: Make sure to rinse extremely well before applying any other **Shield** products to ensure proper paint adhesion.

FEATURES AND BENEFITS



Potent Fungicides:

Contains powerful anti-fungal agents effective against various types of fungi and algae

ADDITIONAL DATA

SHELF LIFE @ 30 °C:

18 months, in the original sealed container, with proper storage conditions. The storing condition is crucial.

HEALTH & SAFETY:

Safety precautions: Generally, most of the water-based paints are quite safe to handle with due precautions. As a general rule, avoid skin and eye contact by wearing overalls, gloves, goggles, and mask etc. Spillage on skin should immediately be removed by thorough washing with water and soap or suitable cleaner. The eye should be flushed with fresh water. Avoid inhalation of vapors and paint mist by wearing a suitable mask. In the event of ingestion and eye contact, seek medical attention immediately. Painting must be carried out in a well-ventilated area.

Local safety regulations to be followed.

STORAGE & HANDLING:

Store at temperatures below 40°C, avoiding direct sunlight to maintain product quality.

Keep the paint container in a sealed condition under shade, away from direct sunlight and extreme temperatures.

Do not keep paint material near any ignition sources.

Do not put back the half or unused material back in the original container, containing the supplied paint, to avoid contamination.

Handle with care.

Stir well before use.

PACKAGING:

Available in 5 L plastic containers.

AZAR GROUP



AZAR CHEMICAL INDUSTRIES LTD

+233 555 333 777

+233 555 333 888

info@azarghana.com

marketing@azargroup-gh.com

Azar Chemical Industries

www.azargroupltd.com